





Model		SC5-Ag				
Features	Dimension L* W * H (mm)	19 * 15.5 * 15.8				
	Terminal Type	РСВ				
	Weight	10g Approximately				
Contact Data	Contact Form	1C				
	Contact Material	Ag Alloy				
	Contact Capacity	7A @300VAC / 10A @120VAC / 10A @28VDC				
	Contact Resistance	100mΩ Max. (at 1A / 6VDC)				
Coil Data	Coil Voltage	3 ~ 48VDC				
	Coil Power Consumption	0.36W		A SECOND		
		Coil Voltage	Coil Resistance (Ω) ±10%	Pull in Voltage Max. (VDC)	Drop Out Voltage Min.(VDC)	
	Coil Specification	6VDC	100	75%	10%	
		12VDC	400	75%	10%	
		24VDC	1600	75%	10%	
General Data	Dielectric Strength	750VAC (Between open Contacts)				
		1500VAC (Between coil & Contacts)				
	Insulation Resistance	100MΩ 500VDC				
	Electrical Life	1 x 10 ⁵				
	Mechanical Life	1 x 10 ⁷				
	Operating Temperature	- 40°C to + 70°C				
Dimension	19 0.3 1 12.2 1 0.4	15.5 5-ø1.3 Softon VIEW BOTTON VIEW (IC) BOTTON VIEW (IC)				
Application	Television, Stereo, Microwave, Air	reo, Microwave, Air Conditioner, Refrigerator, Iron, Electrical Boiler, Satellite Receiver, etc.				